



2026 HAUNTED HUNDRED STREET STOCK OPEN

RULES Section 1. General

1. Eligible Cars: 1975–1992 Rear Wheel Drive American-made cars only.
 2. Minimum Right-Side Weight: 1,400 lbs. (Tech may add weight to maintain equalized competition). See Shock Rule.
 3. No traction control devices permitted.
-

Section 2. Bodies

1. Body Types: 1975–1992 Street Stock type bodies or AR/FS Muscle Car bodies only.
 2. Body Materials: Fiberglass, Plastic, Steel, or Aluminum.
 3. Prohibited: No holes in rear covers, no ABC, downforce, or dirt bodies, noses, or panels. No roof vanes or added panel extensions.
 4. Panning: Not allowed under cars.
 5. Spoilers: Maximum size 60" x 5", mounted to trunk lid. No side boxing.
 6. Windows: Lexan mandatory. Door windows are not permitted. Passenger-side window extension max 12" from A-pillar base.
 7. Exterior Rub Rails: Plastic only, between front and rear tires.
-

Section 3. Chassis

1. Chassis: Stock, Johnson, XYG, or Hamm chassis/clips allowed. No Camaro prefabbed snouts. Suspension must match chassis. No offset chassis. Rear chassis must travel over rear end. No underslung clips. Minimum wheelbase: 108" (+/- 1").
 2. Min – 5" coil springs or steel leaf springs permitted. 3 or 4 link suspension permitted. All rear suspension rods & links must be use solid ends. Upper 3-link may use rubber connection only.
 3. Steering: Stock-type steering boxes only. No rack-and-pinion.
 4. Jacking Bolts: Permitted on all four corners. Adjustable leaf spring mounts permitted. No coil-overs.
 5. Fuel Cell: Minimum bottom height 8" (with driver).
 6. Lead: Allowed for meeting weight rules. No lead inside car. No shifting weight setups.
-

Section 4. Suspension

1. Shocks – Option 1: Max MSRP \$120 each. Stock mount or fixed bearing ends. Restrictions must be: steel, sealed, non-adjustable, no modifications, limiters, or altered specs. Must travel freely.
 2. Shocks – Option 2: Max MSRP \$175 (add 60 lbs.) No Schrader valves. Same restrictions as Option 1.
 3. Shocks: Part numbers must be legible and unaltered or will be deemed illegal.
 4. Ride Height: Minimum 4" chassis ride height with driver in race-ready condition.
 5. Tread Width: Max outside width 72" (measured rim lip-to-lip at spindle height).
Max ½" spacers, must be the same side-to-side.
 6. Sway Bar: Only one-piece bar permitted.
 7. Brakes: Steel single-piston calipers only.
-

Section 5. Wheels & Tires

1. Wheels: Steel racing wheels required, 7" width ONLY. Offset must match left to right. No pressure relief valves.
 2. Tires: 15" American Racer P225/70D15 (705) only. No softening or altering. Must remain dry before, during, and after race. Durometer rule in effect. Tire testing may occur.
-

Section 6. Engines

1. Eligible Engines: GM 305/350, Ford 302/351, Mopar 318/340/360. No aluminum blocks/heads. No fuel injection.
2. Crate Engines: GM 602 Crate allowed only.
3. Engine Location: Must remain in stock centered location.
4. Compression Ratio: Maximum 10.99:1 (checked via whistler).
5. Intakes: Dual plane only unaltered.
6. Carburetor: Any carburetor permitted using a maximum one inch spacer.
7. Air Cleaner: No air boxes or ram/cowl induction. Must fit under hood. No added hood scoops.
8. Exhaust: Stock or headers (max 1-5/8"). No 180, crossover, or Tri-Y headers. Exhaust must exit under car with mufflers.
9. Ignition: Stock OEM-style HEI distributors only. No MSD boxes. MSD rev limiter permitted.
10. Oiling: No dry sump systems.

Section 7. Transmission & Clutch

1. Transmission: 3- or 4-speed standard only. Aluminum or steel. No automatics. Final drive must be 1:1.
 2. Clutch: Stock magnetic steel, 10" minimum single disc. No aluminum.
 3. Flywheel: Stock-type, one-piece, all-steel only.
-

Section 8. Rear End & Driveshaft

1. Rear End: Stock-type or Ford 9" steel center section permitted (full floater allowed). No quick-change units.
2. Differential: locked only. No Truetrac, limited slip, or similar.
3. Gear Rule: Max final drive 6.00.

Section 9. Safety & Miscellaneous

1. Safety Equipment: Cars not allowed on track without defined safety gear.
2. Fire Suit: 1- or 2-piece single layer minimum. Gloves and shoes are required.
3. Helmets: SA-rated, 2010 or newer. Unsafe helmets must be replaced before racing.
4. Harness: Five-point racing harness required, dated within 3 years. Installations must follow manufacturer guidelines.
5. Window Net: Required, ribbon or mesh.
6. Mirrors: Permitted.
7. Radios: Only scanners allowed (receive-only). Track frequency only. No 2-way or outside comms. Track frequency provided at event.
8. Transponders: AMB transponders required. Mounted no further forward than 78" from front wheel centerline.